

Mastertac Technical Information

12-03-2021 EN SI

Product

HIGH GLOSS OP NXT+FSC / PERMANENT / KRAFT 83-FSC / SOLID PRINTED

Sales Code

HWS/94-A/HWV/W1

Product use

Product designed for high-gloss labels with mirror like finish and high opacity, for correcting errors and text changes. Recommended for block-out labels where total coverage is required. The Mastertac NXT+ product design results in a superior carbon performance by leveraging a smarter choice and use of materials.

Typical technical values

Face

HIGH GLOSS OP NXT+FSC

Product

Cast-coated, wood-free paper with grey reverse side to increase the opacity.

Substance

82 g/m² ISO 536

Caliper

80 µm ISO 534

Tensile strength MD

5 kN/m ISO 1924/1

Tensile strength CD

2,9 kN/m ISO 1924/1

Brightness

80 % ISO 2470/1

Roughness

0,7 µm ISO 8791 PPS 10

Opacity

99 % ISO 2471

Gloss

89 % Hunter 75°

CIE Whiteness

103 % ISO 11475

Stiffness MD

0,42 mNm ISO/DP 2493

Stiffness CD

0,25 mNm ISO/DP 2493

Printability

Flexography, letterpress, rotogravure, offset, screen and hot foil.

Sustainability

The product is sold as FSC Mix Credit under UPM Raflatac's FSC™ certificate SGSCHCOC-004879.

Adhesive

PERMANENT

Type

Permanent

Composition

Waterborne acrylic

Use

A very good adhesive for general use with paper labels. Good heat resistance. Improved guillotine properties.

Tack min

10 N FTM 9

Labelling temperature min

5 °C

Service temperature min

-10 °C

Service temperature max

100 °C

Limitations

Should not be used in cold environments. Not recommended for labelling highly curved surfaces.

Backing

KRAFT 83-FSC

Product

White woodfree kraft backing paper

Substance

83 g/m² ISO 536



Mastertac®
by UPM Raflatac

| | | | |
|---------------------|--|------|----------|
| Caliper | 84 | µm | ISO 534 |
| Tensile strength MD | 8,7 | kN/m | ISO 1924 |
| Tensile strength CD | 3,8 | kN/m | ISO 1924 |
| Sustainability | The product is sold as FSC Mix Credit under UPM Raflatac's FSC™ certificate SGSCHCOC-004879. | | |

Performance

| | |
|-------------------------------|--|
| Total caliper | 179 µm |
| Minimum labelling temperature | 5 °C |
| Service temperature | -10 °C +100 °C |
| Shelf life | From date of manufacture: 48 months, under FINAT defined storage conditions (+20-25°C and 40-50% RH). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life. |

Approvals

Approvals For further compliance information related to food labeling applications, please contact your local sales representative for a Declaration of Conformance (DoC) document.

Approvals Toy labeling: This product complies with the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements.

Disclaimer The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

